



Privacy Decorative Slats for Chain Link and Ornamental Fencing

Pexco Tacoma
Tacoma, WA
800.822.7528

Pexco Athol
Athol, MA
800.755.7528

www.pdsfence.com
www.pexco.com
massales@pexco.com



All products proudly made in USA



Privacy Decorative Slats (PDS®) for Chain Link and Ornamental Fencing

For over 30 years, Pexco PDS® HDPE Fence Products has been the largest manufacturer of chain link and ornamental fence enhancement products, marketed under the PDS® brand name. Produced in our west and east coast manufacturing facilities, PDS® Fence Products are available through most fence distributors in the U.S. and Canada.

Materials

Most of our fence products are extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors, specifically designed to retard the harmful effects of the sun and lengthen the life of the product.

Durability

Our fence products are resistant to: severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates and common environmental pollutants.

Maintenance

Pressure cleaning of surface contaminants is quickly accomplished with plain water.

Wind Load Disclaimer

Pexco will not be responsible for fence damage resulting from wind load conditions due to insufficient structural support.

Limited Warranty

Pexco PDS® Fence Products carry an extensive, pro-rata warranty against breakage under normal conditions. See each product page for years of coverage or write Pexco for full warranty information.

Standard Colors*



*Exact representation of slat colors in printing is difficult. Please refer to actual color samples for final matching.

Patents

Covered by one or more of the following U.S. patents:
5,165,664 / 5,184,801 / 5,234,199 / 5,584,468, RE35, 208 / 5,687,957 / 5,806,839 / 6,068,243 / 7,207,551
Covered by one or more of the following Canadian patents:
2,161,852 / 2,186,986 / 2,208,822 / 2,508,189.

Made in the USA



Bottom Lock



Bottom Lock utilizes our patented bottom locking channel system providing a “snap-in” locking effect for security and deters vandalism at an affordable price.

Design

Bottom-lock slats are flat and tubular in shape, with reinforced “legs” inside for extra durability.

Installation Instructions

- Step 1** Insert locking channel horizontally in first full diamond at bottom of fence with open side facing up.
- Step 2** Insert vertical slats with beveled/notched end downward. Slat engages and interlocks with bottom rail.
- Step 3** Push the vertical slat into the horizontal channel to lock in place.

Standard Heights

4, 5, 6, 7, 8, 10 and 12 feet. Special heights available upon request.

Wind Load and Privacy Factor

Approximately 75%.

Slat Length

3½" shorter than overall height of fence.

Bottom-Locking Channel

10 feet provided in each bag.

Warranty 25 years pro-rata.

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag
Bottom Lock 2"	1 ³ / ₃₂ "	2"	8, 9 or 11	82
Bottom Lock 2¼"	1¼"	2¼" or 2 ⁹ / ₁₆ "	11½" or 12½"	78
Bottom Lock 1¾"	7 ¹ / ₈ "	1¾"	8, 9 or 11	97
	7 ⁷ / ₈ "	2"	6	97

Top Lock



Top Lock utilizes a top-locking mechanism located near the top of the slats for easy installation and to ensure a clean, straight edge, enhancing its appearance.

Design

Top-Locking Slats are flat and tubular in shape, with circular, notched-out holes located near the top of the slat.

Installation Instructions

Step 1 No need to kneel, simply insert the slats vertically from top to bottom, keeping the locking holes on top.

Step 2 Thread the flexible locking channel horizontally through the notched holes in the slats. These holes are elliptical to ensure they always stay open for fast and easy threading.

Step 3 For extra security, insert a pop-rivet through locking channel and one slat.

Standard Heights

4, 5, 6, 7, 8, 10 & 12 feet. Special heights available upon request.

Wind Load and Privacy Factor

Approximately 75%.

Slat Length

2" shorter than the overall height of fence.

Flexible, Top-Locking Channel

10 feet provided in each bag.

Warranty 25 years pro-rata.

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag
Top Lock 2"	1 ³ / ₃₂ "	2"	8, 9 or 11	82
Top Lock 2 1/4"	1 1/4"	2 1/4" or 2 3/8"	11 1/2" or 12 1/2"	78
Top Lock 1 3/4"	7/8"	1 3/4"	8, 9, or 11	97
	7/8"	2"	6	97

Winged Slat®



With the proven quality and durability of our standard slats, plus unique "wings" for extra screening and security, the slats are self-locking – no channels are needed!

Design

Our patented Winged Slat has a rigid, flat-tubular body, with "legs" inside for extra support. Flexible and resilient wing portions are positioned on each side of the slat body. Serrations are added to the wings for easier installation and locking power.

Installation Instructions

Insert vertical slats with angle cut end downward. Winged portion interlocks with chain link knuckles.

Standard Heights

4, 5, 6, 7 and 8 feet. For heights exceeding 7 feet, (2) two half sizes (i.e. for 10 ft. fence use two 5 ft. slats) are recommended. This will help during installation and will not lessen privacy.

Wind Load and Privacy Factor

Approximately 90%. (Based on wire/mesh used – stretch tension)

Slat Length

2" shorter than the overall height of fence.

Warranty 25 years pro-rata.

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag
Winged Slat	1 1/4"	2"	9" only	82

LiteLink™



LiteLink is a single wall "M" shaped slat that gives visual screening and color enhancement at our most affordable price. It also uses our patented Bottom-Locking system.

Design

Compact and lightweight, LiteLink's unique shape enables the slat to self stack. It comes packaged in a box, making it easy to ship and efficient to store.

Installation Instructions

Step 1 Insert locking channel horizontally in first full diamond at bottom of fence with open side facing up.

Step 2 Insert vertical slats with interlocking tab downward. Slat engages and interlocks with bottom rail.

Step 3 Push the vertical slat into the horizontal channel to lock in place.

Standard Heights

4, 5, 6, 7, 8, 10 and 12 feet. Special heights available upon request.

Wind Load and Privacy Factor

Approximately 75%.

Slat Length

3½" shorter than overall height of fence.

Bottom-Locking Channel

10 feet provided in each bag.

Warranty

7 years pro-rata.

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Box
LiteLink	1¼"	2", 2¼" or 2⅝"	9, 11 or 11½"	82

Industrial Pre-Woven



Industrial Pre-Woven is a uniquely styled slat that is mechanically inserted into the chain link wire during the weaving process. Once inserted, the wire is finished above and below the slat (either bow-knuckle or knuckle-over).

Design

Industrial pre-woven slats are flat and tubular in shape, with reinforced "legs" inside for extra durability.

Installation

Because this slat comes pre-inserted in the chain link fabric, just stretch the wire and tie it up. The result is a fully slatted fence with sight reduction.

Standard Heights

4, 5, 6, 7, 8, 10 and 12 feet. Special heights available upon request.

Wind Load and Privacy Factor

Approximately 75%.

Upon Special Request

Available in bags that cover 25 linear feet for hand installation jobs.

Note

Pexco is the manufacturer of the slats only. We do not weave the wire. For pre-woven products please contact your fence supplier or contact us for a supplier near you.

Warranty

25 years pro-rata.

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Crate	Approx. Coverage Per Crate
Industrial	2⅝"	3½" x 5"	9 or 10	2014 (106 pieces per bag)	475 linear feet

HedgeLink™



HedgeLink is a unique chain link fence enhancement, creating a natural hedge look that requires no maintenance.

Design

Core is made with 16-gauge, braided galvanized wire. Blue Spruce colored needles are made with 3-mil PVC.

Installation

Requires no locking device or tools and installs much like our Winged Slats® – installing vertically from top to bottom. Insert HedgeLink slats vertically top to bottom, with angle cut end downward, while revolving the slat clockwise with your fingers for easier installation.

Standard Heights

4, 5, 6, 7, 8 and 10 feet.

Fence Size

For most fence sizes. Not intended for use with mini-mesh wire.

Wind Load and Privacy Factor

Approximately 90%.

Features

UV stabilized to protect against the harmful rays of the sun. Flame retardant.

Note

Do not mix HedgeLink with any other manufacturer's inferior hedge product – color shades are different.

Warranty 10 years pro-rata.

Slat Type	Mesh Size	Wire Gauge	Slats Per Box	Approx. Coverage Per Box
HedgeLink	2", 2¼" or 2⅜"	9,11 or 11½"	82	10 linear feet

Safety Top Cap™



Safety Top Cap™ serves two purposes. First, the unique design provides protection against bodily injury by covering the exposed knuckles or barbs on top of chain link fences. Second, it displays nicely as a decorative trim piece complementing any chain link fence system.

Design

Durable and flexible plastic in an open tubular shape.

Installation

Simply "snap" over the top of the fence and lock to the wire mesh with steel hog-rings (included) through the (3) three pre-drilled holes on each piece.

Multiple Uses

Primarily used in our safety yellow color for baseball outfields. This product is also growing in popularity at athletic fields, parks, playgrounds and recreational facilities throughout the country.

Security

Resists vandalism by using the hog-rings to permanently attach the Safety Top Cap to the fence.

Colors

Safety Top Cap colors include our standard slat colors and the 2 additional colors shown here.



Warranty 25 years pro-rata.

Cap Height	Cap Width	Cap Length	Contents Per Bag	Coverage Per Bag
5½"	2¼"	8'	5 top caps 15 hog-rings	40 linear feet

FinLink®



The FinLink® slat offers an increased degree of coverage with a unique configuration of (3) three privacy fins.

Design

Our unique patented design includes a rigid, flat tubular body, with “legs” inside for extra support. Three flexible fins (two on one side and one on the other) are positioned on the sides of the slat body. The FinLink fins are not serrated, thus providing a smooth finished look.

Installation Instructions

Step 1 Insert locking channel horizontally in first full diamond at bottom of fence with open side facing up.

Step 2 Insert vertical slats with bevel end downward.

Step 3 Push the vertical slat into the horizontal channel until securely to the bottom of channel.

Standard Heights

4, 5, 6, 7 and 8 feet.

Wind Load and Privacy Factor

Approximately 90%.

Slat Length

3½" shorter than overall height of fence.

Bottom-Locking Channel

10 feet provided in each bag.

Warranty 25 years pro-rata.

Slat Type	Slat Width	Mesh Size	Wire Gauge	Slats Per Bag
FinLink	1⅜"	2", 2¼" or 2⅜"	11	82

Fence Weave®



Fence Weave® is the do-it-yourself solution for homeowners looking to easily turn their ordinary chain link fence into an attractive and efficient privacy enclosure.

Design

Fence weave slats are created out of flexible polyethylene extrusion (LDPE) and are available in a wide range of attractive colors.

Installation

Simply weave our product into chain link fence, cut and fasten with the provided copper fasteners for easy installation.

Standard Heights

Each roll is 250 feet long and covers 40 square feet.

Wind Load and Privacy Factor

Approximately 70%.

Warranty 5 years pro-rata.

Slat Type	Slat Width	Mesh Size	Wire Gauge	Approx. Coverage Per Box
Fence Weave	1⅞"	2", 2¼" or 2⅜"	9, 11, 11½ or 12½	40 square feet